


50% REDUCTION OF ENERGY CONSUMPTION
UP TO 20.000 KG PER YEAR REDUCTION OF CO2 EMISSION
UP TO 3.500 EURO PER YEAR REDUCTION OF ELECTRICITY COSTS



f^ower[®]
ecologyintesting

YOUR RESPECT FOR A SUSTAINABLE PLANET



flower®

YOUR RESPECT FOR A SUSTAINABLE PLANET

Flower®, for a better future

Environmental protection and preservation are among the highest priorities for a company having ISO14001 certification. In keeping faith with sustainability policies Angelantoni Industrie has been conducting research and development related to reduce energy consumption and to use ecological and recyclable materials in order to develop products that reduce environmental damages at all stages of the product lifecycles.

The new chamber, called "flower®", is the first result of this research, a truly innovative product in the field of climatic test chambers, thanks to its special design.

Reduced energy consumption

About 50% reduction of energy consumption can be assured during the stabilization phases due to a unique and "patented" system which includes:

- an inverter that controls compressor speed and allows the adaptation of compressor power to different working needs
- a "cold sink" to increase the cooling efficiency.

Reduced noise level

50% noise reduction is obtained due to:

- an inverter on the compressor which reduces the rotation speed to about 40% of its nominal value according to working conditions
- an automatic control system that reduces condenser blower rotating speed according to ambient temperature and cooling power.

These advantages are combined with the use of "environmentally friend" materials during production phases:

- no polyurethane in the insulation process
- recyclable or easily disposable packing materials.

© Angelantoni Industrie SpA - October 2010

	FLOWER 340	FLOWER 340 C	FLOWER 600	FLOWER 600 C	FLOWER 1200	FLOWER 1200 C
Useful capacity	336	336	559	559	1152	1152
Int. Dims (WxDxH)	601X810X692	601X810X692	850x740x890	850x740x890	1000x1130x1020	1000x1130x1020
Ext. Dims (WxDxH castors included)	919X1817X1638	919X1817X1638	1168x1797x2021	1168x1797x2021	1320x2235x2137	1320x2235x2137
Max electrical power (kW)	11	13	13,5	16,5	18,5	22
Max electrical power (kW) at steady conditions	2,5	4	4	7	4,9	8
Max noise (dba)*	59	64	64	67	65	69
Max noise (dba)* at steady conditions	54	57	57	61	60	64
Weight	850	900	1030	1130	1230	1330
R.H. Range within the Temp. Range +5°C/+95°C	10%...98%	10%...98%	10%...98%	10%...98%	10%...98%	10%...98%
Temp. Range	-40°C/+180°C	-70°C/+180°C	-40°C/+180°C	-70°C/+180°C	-40°C/+180°C	-70°C/+180°C
Temperature Rate of Change measured at the control probe**						
heating	8 K/min	8 K/min	6 K/min	6 K/min	6 K/min	6 K/min
cooling without the "cold sink" device	3 K/min	2 K/min	4 K/min	4 K/min	4 K/min	3 K/min
cooling with the "cold sink" device	6 K/min	3,8 K/min	8 K/min	7 K/min	7 K/min	5 K/min

* measured at 1 meter from the front wall in a non reverberating room ** according to IEC 60068-3-5 and IEC 60068-3-6



Loc. Cimacolle, 464 - 06056 Massa Martana (Pg) - Italy Tel. +39 075.89551 (a.r.) Fax +39 075.8955200
 info@angelantoni.it www.angelantoni.it

www.ideastrategie.com